PRODUCT	PLAN MARK	FIXTURE	DESCRIPTION	WASTE SIZE	MODEL NO.
	ECO-1	EXTERIOR CLEANOUT	SIOUX CHIEF 834-4DNRVH FINISHLINE FLOOR CLEANOUT, ADJUSTABLE CAST IRON BODY, POLYPROPYLENE PLUG, AND ADJUSTABLE, 6-1/2" ROUND, VANDAL PROOF, SPECIAL DUTY NICKEL BRONZE COVER. ADJUSTABLE BEFORE AND AFTER POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	834-3DNRVH
				4"	834-4DNRVH
				6"	834-6DNRV
	ECO-1	EXTERIOR CLEANOUT	SIOUX CHIEF 850-9i CAST IRON DOUBLE FLANGED HOUSING WITH HEAVY DUTY SECURED SCORIATED CAST IRON COVER WITH LIFTING DEVICE AND 858-64L CLEANOUT BODY PUSH JOINT WITH 878-40 POLYPROPYLENE PLUG	–	850-9i
			PUSH-JOINT X FIP ADAPTER - 858-64L	4"	858-64L
			SLOTTED POLYPRO FLUSH PLUG - 878-40	4"	878-40
			SLOTTED POLYPRO FLUSH PLUG - 878-60	4"	878-60
	FCO-1	FLOOR CLEANOUT	SIOUX CHIEF 834-4DNR FINISHLINE FLOOR CLEANOUT, ADJUSTABLE CAST IRON BODY, POLYPROPYLENE INTERNAL CLEANOUT PLUG, 6-1/2" ROUND SCORIATED NICKEL BRONZE COVER WITH NO-HUB OUTLET. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	834-3DNR
				4"	834-4DNR
				6"	834-6DNR
	FCOH	FLOOR CLEANOUT HEAVY DUTY	SIOUX CHIEF 834-4DNRH FINISHLINE FLOOR CLEANOUT, ADJUSTABLE CAST IRON BODY, POLYPROPYLENE INTERNAL CLEANOUT PLUG, ROUND SCORIATED NICKEL BRONZE SPECIAL DUTY COVER, NO HUB OUTLET. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR.	3"	834-3DNRH
				4"	834-4DNRH
	FCO-1	FLOOR CLEANOUT STAINLESS STEEL	SIOUX CHIEF 834-4SSR FLOOR CLEANOUT - ADJUSTABLE STAINLESS STEEL BODY, POLYPROPYLENE INTERNAL CLEANOUT PLUG, 6-1/2" ROUND SCORIATED STAINLESS STEEL COVER WITH NO-HUB OUTLET. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR	3"	834-3SSR
				4"	834-4SSR
	FD-1	FLOOR DRAIN	SIOUX CHIEF 833-225NR FINISHLINE FLOOR DRAIN, CAST IRON BODY AND CLAMPING COLLAR, ADJUSTABLE 5-1/2" ROUND HEEL PROOF NICKEL BRONZE STRAINER AND NO HUB OUTLET. ADJUSTABLE BEFORE AND AFTER POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	833-225NR
				3"	833-235NR
				4"	833-24NR
	FD-1	FLOOR DRAIN	SIOUX CHIEF 832-4DNR FINISHLINE FLOOR DRAIN, ADJUSTABLE CAST IRON BODY, 6-1/2" ROUND NICKEL BRONZE STRAINER WITH NO-HUB OUTLET. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	833-25DNR
				3"	832-3DNR
				4"	832-4DNR
	FD-1	FLOOR DRAIN HEAVY DUTY	SIOUX CHIEF 833-4DiR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH CLAMPING COLLAR AND ADJUSTABLE 6-1/2" ROUND HEAVY DUTY DUCTILE IRON RING & STRAINER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	833-22DiR
				3"	833-23DiR
				4"	833-24DiR
	FD-1	FLOOR DRAIN ABOVE GRADE ON METAL DECK	SIOUX CHIEF 822-F2DNR FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE, ADJUSTABLE CAST IRON BODY, 5-1/2" ROUND NICKEL BRONZE STRAINER WITH NO HUB OUTLET. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. USE 822-EX3 THREADED EXTENSIONS UNDER CORING SLEEVE FOR CONCRETE POURS OF 4" OR MORE.	2"	822-F2DNR
				3"	822-F3DNR
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER CORING SLEEVE TO EXTEND UP TO 4" THICK POUR.	–	822-EX3
	FD-2	FLOOR DRAIN STAINLESS STEEL	SIOUX CHIEF 832-4SSRM FINISHLINE FLOOR DRAIN, ADJUSTABLE STAINLESS STEEL BODY, 6-1/2" ROUND STAINLESS STEEL STRAINER WITH NO-HUB OUTLET. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	832-3SSRM
				4"	832-4SSRM
	FD-2	FLOOR DRAIN EQUIPMENT ROOM	SIOUX CHIEF 832-49DF FINISHLINE CAST IRON DRAIN BODY, 832-SD9 LOOSE 9" ROUND HEAVY DUTY CAST IRON HEEL PROOF GRATE, NO HUB BOTTOM OUTLET. ADJUSTABLE BEFORE AND AFTER POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	4"	832-49DF
				6"	832-6DF
			LOOSE 9" ROUND HEAVY DUTY CAST IRON GRATE	–	832-SD9
	FD-2	FLOOR DRAIN EQUIPMENT ROOM	SIOUX CHIEF 860-4PZ2S LARGE CAPACITY PVC FLOOR DRAIN WITH ANCHOR FLANGE, 9-3/4" ROUND HEEL PROOF STAINLESS STEEL OPEN HALF GRATE AND SEDIMENT BUCKET	2"	860-2PZ2S
				3"	860-3PZ2S
				4"	860-4PZ2S
				6"	860-6PZ2S
	FD-2	FLOOR DRAIN	SIOUX CHIEF # 860-R264iB, 4" DEEP CAST IRON BODY, 12" ROUND, LOOSE, HEAVY DUTY, DUCTILE IRON GRATE, SEDIMENT BUCKET, NO HUB BOTTOM OUTLET, SEEPAGE PAN, AND MEMBRANE FLASHING CLAMP. PROVIDE TRAP PRIMER PORT IF TRAP PRIMER IS PROVIDED IN DRAWINGS. USE OUTLET SIZE AS SHOWN ON PLANS.	2"	860-R222iB
				3"	860-R223iB
				4"	860-R224iB
				6"	860-R226iB
				8"	860-R228iB
	FS-1	FLOOR SINK	SIOUX CHIEF 861-QF2326N2BC, 6" DEEP CAST IRON BODY WITH ACID RESISTING ENAMELED INTERIOR, ANCHOR FLANGE WITH SEEPAGE HOLES, CLAMPING COLLAR, ALUMINUM SEDIMENT BUCKET, AND 12" SQUARE NICKEL BRONZE RIM AND HALF GRATE. NO HUB OUTLET	2"	861-QF2226N2BC
				3"	861-QF2326N2BC
				4"	861-QF2426N2BC
	FS-1	FLOOR SINK	SIOUX CHIEF 861-QF2328N2BC, 8" DEEP CAST IRON BODY WITH ACID RESISTING ENAMELED INTERIOR, ANCHOR FLANGE WITH SEEPAGE HOLES, CLAMPING COLLAR, ALUMINUM SEDIMENT BUCKET, AND 12" SQUARE NICKEL BRONZE RIM AND HALF GRATE. NO HUB OUTLET	2"	861-QF2228N2BC
				3"	861-QF2328N2BC
				4"	861-QF2428N2BC
	FS-1	FLOOR SINK	SIOUX CHIEF 861-QF2321N2BC, 10" DEEP CAST IRON BODY WITH ACID RESISTING ENAMELED INTERIOR, ANCHOR FLANGE WITH SEEPAGE HOLES, CLAMP COLLAR, ALUMINUM SEDIMENT BUCKET, AND 12" SQUARE NICKEL BRONZE RIM AND HALF GRATE. NO HUB OUTLET	2"	861-QF2221N2BC
				3"	861-QF2321N2BC
				4"	861-QF2421N2BC
	FS-1	FLOOR SINK	SIOUX CHIEF # 861-QF2386A CAST IRON BODY WITH ACID RESISTING ENAMELED INTERIOR, ANCHOR FLANGE WITH SEEPAGE HOLES AND 8" X 8" SQUARE GRATE.	2"	861-QF2286A
				3"	861-QF2386A
				4"	861-QF2486A
	HD-1	HUB DRAIN	SIOUX CHIEF 833-23DF CAST IRON DRAIN BODY WITH CLAMPING COLLAR AND ADJUSTABLE CORING SLEEVE AND TEMPORARY COVER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL 832-4HHD ADJUSTABLE HUB FINISH FIXTURE WITH 832-UM STAINLESS STEEL DEBRIS BASKET	2"	833-22DF
				3"	833-23DF
				4"	833-24DF
			ADJUSTABLE HUB DRAIN FIXTURE 832-4HHD	–	832-4HHD
			STAINLESS STEEL MESH DEBRIS BASKET 832-UM	–	832-UM
	FFD-1	FUNNEL FLOOR DRAIN	SIOUX CHIEF 833-225NR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH CLAMPING COLLAR AND ADJUSTABLE 5-1/2" ROUND NICKEL BRONZE RING & STRAINER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. PROVIDE WITH 863-FA FUNNEL	2"	833-225NR
				3"	833-235NR
				4"	833-24NR
			CONDENSATE FUNNEL 863-FA	–	863-FA
	BWV	BACKWATER VALVE	SIOUX CHIEF PROCHECK BACKWATER VALVE WITH PVC BODY, CARRIER AND FLAPPER. FLAPPER ALLOW UNRESTRICTED, UNIDIRECTIONAL FLOW. VALVE DESIGN TO BE ADAPTABLE TO SHALLOW OR DEEP-BURY INSTALLATIONS.	3"	869-S3P
				4"	869-S4P
			BACKWATER VALVE WITH PVC BODY, LID AND FLAPPER - 869-2P	2"	869-2P
			BACKWATER VALVE WITH PVC BODY, LID AND FLAPPER - 869-6P	6"	869-6P
	ORD-1	OVERFLOW ROOF DRAIN	SIOUX CHIEF # 868-524SCEW, 15" DIAMETER CAST IRON OVERFLOW ROOF DRAIN, FLASHING CLAMP, 2" HIGH EXTERNAL WATER DAM, SUMP RECEIVER, UNDERDECK CLAMP, NO HUB OUTLET AND SECURED CAST IRON DOME. ADJUSTABLE THREADED EXTENSION TO MATCH INSULATION THICKNESS.	3"	868-523SCEW
				4"	868-524SCEW
				6"	868-526SCEW
				8"	868-528SCEW
	RD-1	ROOF DRAIN	SIOUX CHIEF # 868-524SCE, 15" DIAMETER CAST IRON ROOF DRAIN, GRAVEL GUARD FLASHING CLAMP, SUMP RECEIVER, UNDERDECK CLAMP, NO HUB OUTLET AND SECURED CAST IRON DOME. ADJUSTABLE THREADED EXTENSION TO MATCH INSULATION THICKNESS.	3"	868-523SCE
				4"	868-524SCE
				6"	868-526SCE
				8"	868-528SCE
	ORD-2	OVERFLOW ROOF DRAIN	SIOUX CHIEF 868-2010USW CAST IRON 20" DIAMETER OVERFLOW ROOF DRAIN WITH FLASHING CLAMP, 2" EXTERNAL WATER DAM AND CAST IRON LOCKING DOME. PROVIDE SUMP RECEIVER, UNDER-DECK CLAMP	10"	868-2010USW
				12"	868-2012USW

PRODUCT	PLAN MARK	FIXTURE	DESCRIPTION	WASTE SIZE	MODEL NO.
	RD-2	ROOF DRAIN	SIOUX CHIEF 868-2010US CAST IRON 20" DIAMETER ROOF DRAIN WITH GRAVEL GUARD FLASHING CLAMP AND CAST IRON LOCKING DOME. PROVIDE SUMP RECEIVER, UNDER-DECK CLAMP.	10"	868-2010US
				12"	868-2012US
	OD-3	OVERFLOW ROOF DRAIN	SIOUX CHIEF 868-i4W CAST IRON 11" DIAMETER ROOF DRAIN WITH FLASHING CLAMP AND 2" HIGH EXTERNAL WATER DAM, SECURED POLYPROPYLENE DOME. PROVIDE SUMP RECEIVER, UNDERDECK CLAMP AND EXTENSION COLLAR KIT.	3"	868-i3WUES
				4"	868-i4WUES
				6"	868-i6WUES
	RD-3	ROOF DRAIN	SIOUX CHIEF 868-i4 CAST IRON 11" DIAMETER ROOF DRAIN WITH GRAVEL GUARD FLASHING CLAMP, SECURED POLYPROPYLENE DOME. PROVIDE SUMP RECEIVER, UNDERDECK CLAMP AND EXTENSION COLLAR KIT.	3"	868-i3UES
				4"	868-i4UES
				6"	868-i6UES
	PD-1	PLANTER DRAIN	SIOUX CHIEF 867-L3PP MULTI-LEVEL PLANTER DRAIN, PVC BODY, FLASHING COLLAR WITH SEEPAGE OPENINGS AND SECURED U.V. RESISTANT POLYPROPYLENE DOME WITH STAINLESS STEEL MESH SCREEN AND 4" PERFORATED ADJUSTABLE LENGTH STANDPIPE, SCH. 40 HUB OUTLET	3"	867-L3PP
				4"	867-L4PP
	PD-2	PLANTER DRAIN	SIOUX CHIEF 867-P3P PLANTER DRAIN, PVC BODY, FLASHING COLLAR WITH SEEPAGE OPENINGS AND SECURED U.V. RESISTANT POLYPROPYLENE DOME WITH STAINLESS STEEL MESH SCREEN AND 4" SCH. 40 HUB OUTLET	3"	867-P3P
				4"	867-P4P
	DSC-1	DOWNSPOUT COVER	SIOUX CHIEF 868-N4S ROUND FABRICATED STAINLESS STEEL FRAME WITH FABRICATED SECURED PERFORATED STAINLESS STEEL HINGED COVER	3"	868-N3S
				4"	868-N4S
				6"	868-N6S
				8"	868-N8S
	DSN-1	DOWNSPOUT NOZZLE	SIOUX CHIEF 868-N4H CAST NICKEL BRONZE DOWNSPOUT NOZZLE WITH NO-HUB CONNECTION AND FLANGED TO SECURE NOZZLE TO WALL. PROVIDE 868-NS4 STAINLESS STEEL SCREEN	3"	868-N3H
				4"	868-N4H
				6"	868-N6H
				8"	868-N8H
			STAINLESS STEEL MESH PROTECTION SCREEN FOR DOWNSPOUT NOZZLE	3"	868-NS3
				4"	868-NS4
				6"	868-NS6
				8"	868-NS8
	TD-1	TRENCH DRAIN CLASS A15 (DECORATIVE)	SIOUX CHIEF 865-S1 FASTTRACK HDPE SLOPED TRENCH DRAIN, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-EO CAP/OUTLET, 865-EG STAINLESS STEEL EDGE GUARDS AND 865-GSA DIAGONAL SLOTTED STAINLESS STEEL, LOAD CLASS A, ADA COMPLIANT HEEL PROOF GRATE.	4"	865-S1
				4"	865-S2
			STAINLESS STEEL EDGE GUARDS - 36" - PAIR	–	865-EG
			DIAG-SLOT SS TRENCH DRAIN GRATE - ADA / HEEL-RESISTANT	–	865-GSA
			END CAP / END OUTLET	4"	865-EO
	TD-2	TRENCH DRAIN CLASS D400	SIOUX CHIEF 865-S1 FASTTRACK HDPE SLOPED TRENCH DRAIN, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-EO CAP/ OUTLET, 865-F DUCTILE IRON GRATE FRAME AND 865-GIS HEAVY-DUTY SLOTTED DUCTILE IRON, LOAD CLASS D, GRATE.	4"	865-S1
				4"	865-S2
			HEAVY-DUTY DUCTILE IRON GRATE FRAME - 36"	–	865-F
			HEAVY-DUTY SLOTTED DUCTILE IRON TRENCH DRAIN GRATE - CLASS D400	–	865-GIS
			END CAP / END OUTLET	4"	865-EO
	TD-3	TRENCH DRAIN CLASS A15	SIOUX CHIEF 865-S1 FASTTRACK HDPE SLOPED TRENCH DRAIN, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-EO CAP/ OUTLET, 865-F DUCTILE IRON GRATE FRAME AND 865-GIS HEAVY-DUTY SLOTTED DUCTILE IRON, LOAD CLASS D, GRATE.	4"	865-S1
				4"	865-S2
			SLOTTED REINFORCED POLYPRO TRENCH DRAIN GRATE - ADA / HEEL-RESIST.	–	865-GHC
			END CAP / END OUTLET	4"	865-EO
	TD-4	TRENCH DRAIN CLASS A15 (DECORATIVE) FOR DEPTH-RESTRICTED	SIOUX CHIEF 865-NS1 FASTTRACK HDPE SHALLOW TRENCH DRAIN, 3-3/4" TALL, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-NSC END CAPS, 865-EG STAINLESS STEEL EDGE GUARDS AND 865-GSA DIAGONAL SLOTTED STAINLESS STEEL, LOAD CLASS A, ADA COMPLIANT HEEL PROOF GRATE	4"	865-NS1
			STAINLESS STEEL EDGE GUARDS - 36" - PAIR	–	865-EG
			DIAG-SLOT SS TRENCH DRAIN GRATE - ADA / HEEL-RESISTANT	–	865-GSA
			END CAP	4"	865-NSC
	TD-5	TRENCH DRAIN CLASS D400 FOR DEPTH-RESTRICTED	SIOUX CHIEF 865-NS1 FASTTRACK HDPE SHALLOW TRENCH DRAIN, 3-3/4" TALL, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-NSC END CAPS, 865-F DUCTILE IRON GRATE FRAME AND 865-GIS HEAVY-DUTY SLOTTED DUCTILE IRON, LOAD CLASS D, GRATE.	4"	865-NS1
			HEAVY-DUTY DUCTILE IRON GRATE FRAME - 36"	–	865-F
			HEAVY-DUTY SLOTTED DUCTILE IRON TRENCH DRAIN GRATE - CLASS D400	–	865-GIS
			END CAP	–	865-NSC
	SH-1	LINEAR SHOWER DRAIN	SHOWER PAN DRAIN WITH 30" LINEAR HEAD - STAMPED STAINLESS STEEL SQUARE HOLE STRAINER	2"	823-TX30SP
	SH-2	SHOWER DRAIN	SIOUX CHIEF 825-27P SHOWER MODULE DRAIN WITH STAINLESS STEEL SNAP ON STRAINER	2"	825-27P
	SH-2	SHOWER DRAIN	FIELD-TILED FLOOR WITH SIOUX CHIEF 821-T200PCQ SQUARE TILE COMPATIBLE SHOWER DRAIN WITH PVC BODY, REVERSABLE COLLAR, AND 4-1/2" SQUARE POLISHED STAINLESS STEEL STRAINER	2"	821-T200PCQ
	FSTD-1	FREESTANDING TUB DRAIN	SIOUX CHIEF 819-2P PVC FREESTANDING TUB DRAIN KIT. INCLUDES DRAIN BODY, TEST PLUG, TAILPEICE AND TAILPIECE GASKET	2"	819-2P
		URINAL CARRIER	PLATE-TYPE URINAL CARRIER	–	837-7D
		WATER CLOSET CARRIER	SINGLE ADJUSTABLE HORIZONTAL WATER CLOSET CARRIER RATED FOR 500LB - LEFT-HAND - NO-HUB	4"	837-HSLT
			SINGLE ADJUSTABLE HORIZONTAL WATER CLOSET CARRIER RATED FOR 500LB - RIGHT-HAND - NO-HUB	4"	837-HSRT
			DOUBLE ADJUSTABLE HORIZONTAL WATER CLOSET CARRIER RATED FOR 500LB - BACK-TO-BACK - NO-HUB	4"	837-HSDT
			TILING FRAME FOR WATER CLOSET CARRIER	–	837-TF
		LAVATORY CARRIER	CONCEALED-ARM LAVATORY CARRIER WITH 18" ARMS	–	837-7C18
		WATER COOLER CARRIER	PLATE-TYPE WATER COOLER CARRIER - SIDE x SIDE - SINGLE PLATE	–	837-7P2
	WHA	WATER HAMMER ARRESTER	SIOUX CHIEF 652-A HYDRARESTER, PISTON-TYPE WATER HAMMER ARRESTER WITH HARD DRAWN COPPER BODY, LUBRICATED, DUAL EPDM O-RING SEALS, AND ASSE 1010 CERTIFICATION. PROVIDE SIZE "A", UNLESS SHOWN OTHERWISE ON THE PLANS. CAN BE INSTALLED AT ANY ANGLE. NO ACCESS PANEL REQUIRED.	–	652-A (1/2")
				–	652-AS (1/2")
				–	653-B (3/4")
				–	653-BS (3/4")
				–	654-C (1")
				–	654-CS (1")
				–	655-D (1")
				–	655-DS (1")
				–	656-E (1")
				–	656-ES (1")
				–	657-F (1")
				–	657-FS (1")

PRODUCT	PLAN MARK	FIXTURE	DESCRIPTION	WASTE SIZE	MODEL NO.
	TRIM	P-TRAPS	CHROME PLATED P-TRAP WITH CLEANOUT, 17-GA BRASS 1-1/4" WITH SHALLOW ESCUTCHEON	1-1/4"	240-0453C04
			CHROME PLATED P-TRAP WITH CLEANOUT, 17-GA BRASS 1-1/2" WITH SHALLOW ESCUTCHEON	1-1/2"	240-0463C04
			CHROME PLATED P-TRAP WITH CLEANOUT, 17-GA BRASS 1-1/4" INLET X 1-1/2" OUTLET P-TRAP WITH SHLW ESCUT	1-1/4" X 1-1/2"	240-0487C04
		GRID STRAINERS	1-1/4" x 8" WITH OVERFLOW 17-GA CHROME PLATED CAST BRASS BODY WITH TAILPIECE AND BRASS NUT	1-1/4"	290-20514C04
			1-1/4" WHEELCHAIR OPEN GRID STRAINER 17-GA CHROME PLATED CAST BRASS BODY WITH OFFSET TAILPIECE, OVERFLOW AND BRASS NUT	1-1/4"	290-20515C04
		SUPPLY STOPS	LOOSE KEY COMPRESSION ANGLE STOP, CHROME PLATED, 5/8" O.D. COMPRESSION X 3/8" O.D. COMPRESSION	–	134-G2C1CLK04
			1/2" CTS METAL SHALLOW ESCUTCHEONS CHROME	–	910-2PK2
			LAVATORY SUPPLY TUBE CHROME PLATED COPPER 3/8" O.D. X 12" LONG	–	283-S04112C00
	TP-1	TRAP SEAL PROTECTION DEVICE	SIOUX CHIEF 835-2 TRAPSHIELD BARRIER TYPE TRAP SEAL DEVICE, COMPLIES WITH ASSE 1072 AF-GW	2"	835-2
				3"	835-3
				4"	835-4
	TP-1	TRAP PRIMER TAILPIECE	SIOUX CHIEF 213-092 GRAVITY FEED LAVATORY SINK TAILPIECE TRAP PRIMER. 1/2" NOMINAL BRANCH CONNECTION. CERTIFIED BY ASSE 1044.	1-1/2"	200-092
				1-1/4"	213-096
	TP-1	PRESSURE ACTIVATED TRAP PRIMER	SIOUX CHIEF 695-01 MECHANICAL TRAP PRIMER. 1/2" FIP INLET X 1/2" MIP OUTLET WITH INTEGRAL VACUUM BREAKER. INSTALL VALVE A MINIMUM OF 18" ABOVE FINISHED FLOOR OR ACCESSIBLE IN THE CEILING. SPLITTER# 695-Y53 AND DISTRIBUTOR# 695-D432F	–	695-01
			SPLITTER 695-Y52	–	695-Y52
	TP-1	ELECTRONIC TRAP PRIMER	SIOUX CHIEF 695-ES01 ELECTRONIC TRAP PRIMER WITH 1/2"" INLET AND 1/2"" OUTLET, SOLENOID VALVE ACTUATOR, VACUUM BREAKER HOLES AND CONTROL PANEL WITH INTEGRAL TIMER. INSTALL THE VALVE AND CONTROL PANEL ABOVE CEILING. ELECTRICAL REQUIREMENTS: 120V 1PH AT 1 FLA	–	695-ES01
			SPLITTER 695-Y52	–	695-Y52
	ETP-1	ELECTRONIC TRAP PRIMER SURFACE MOUNT	SIOUX CHIEF 695-ES05 WITH 1/2" INLET AND OUTLET, SOLENOID VALVE ACTUATOR, INTEGRAL VACUUM BREAKER AND CONTROL PANEL WITH INTEGRAL TIMER. TRAP PRIMER SHALL BE MOUNTED IN STEEL ACCESS BOX. ELECTRICAL REQUIREMENT - CONNECT UNIT TO 120V AC SUPPLY.	–	695-ES05
			ELECTRONIC TRAP PRIMER SURFACE MOUNT BOX 10 PORTS	–	695-ES10
			ELECTRONIC TRAP PRIMER SURFACE MOUNT BOX 15 PORTS	–	695-ES15
			ELECTRONIC TRAP PRIMER SURFACE MOUNT BOX 20 PORTS	–	695-ES20
			ELECTRONIC TRAP PRIMER SURFACE MOUNT BOX 30 PORTS	–	695-ES30
	ETP-1	ELECTRONIC TRAP PRIMER RECESSED BOX	SIOUX CHIEF 695-ER05 WITH 1/2" INLET AND OUTLET, SOLENOID VALVE ACTUATOR, INTEGRAL VACUUM BREAKER, CONTROL PANEL, INTEGRAL TIMER. ELECTRICAL REQUIREMENT - CONNECT UNIT TO 120V AC SUPPLY.	–	695-ER05
			ELECTRONIC TRAP PRIMER RECESSED BOX 10 PORTS	–	695-ER10
			ELECTRONIC TRAP PRIMER RECESSED BOX 15 PORTS	–	695-ER15
			ELECTRONIC TRAP PRIMER RECESSED BOX 20 PORTS	–	695-ER20
			ELECTRONIC TRAP PRIMER RECESSED BOX 30 PORTS	–	695-ER30
			14" X 14" STAINLESS STEEL ACCESS COVER	–	971-1414
	CD-1	CONDENSATE DRAIN TAILPIECE	SIOUX CHIEF 206-066 CHROME PLATED BRASS 1-1/2" TAILPIECE WITH 1/2" NOMINAL BRANCH TO DRAIN CONDENSATE.	1-1/2"	206-066
	CDB-1	CONDENSATE DRAIN BOX	SIOUX CHIEF 696-3F DRAIN BOX WITH 2" WASTE OUTLET, 696-CF SECONDARY DRAINAGE FUNNEL AND 696-SC SOLID FRAME INSERT. USED TO DRAIN CONDENSATE IN THE WALL INSTEAD OF INTO A FLOOR DRAIN	2"	696-3F
			DRAINAGE FUNNEL 696-CF	–	696-CF
			SOLID COVER 696-SC	–	696-SC
			LOUVERED COVER 696-LC	–	696-LC
			FRAME EXTENSION 1/2" FOR THICKER WALLS 696-EX	–	696-EX
			FIRE-RATED BOX 696R3	2"	696R3
	WCO	WALL CLEANOUT	CAST IRON CLEANOUT TEE WITH TAPPED BRASS PLUG	3"	853-T23i
				4"	853-T24i
				6"	853-T26i
				8"	853-T28i
			CAST IRON CLEANOUT FERRULE WITH TAPPED BRASS PLUG	3"	853-F23i
				4"	853-F24i
				6"	853-F26i
			SIOUX CHIEF 873-6 COVER KIT 6" POLISHED STAINLESS STEEL COVER AND STAINLESS STEEL SCREW. PRODIVDE 8" COVER OR 10" COVER FOR LARGER SIZE PLUGS.	–	873-6
				–	873-8
				–	873-10
	WMB-1	WASHING MACHINE OUTLET BOX	SIOUX CHIEF 696-G2313MF OXBOX WASHING MACHINE BOX, 1/2" MIP/SWEAT INLET CONNECTIONS, QUARTER TURN VALVES WITH ARRESTERS AND 3/4" MALE HOSE THREAD OUTLET, AND 2" DRAIN OUTLET. USE 696RG2313MF WHEN INSTALLED IN FIRE-RATED WALLS	2"	696-G2313MF
					696RG2313MF
	IM-1	ICE MAKER OUTLET BOX	SIOUX CHIEF 696-G1010MF OXBOX ICE MAKER BOX, QUARTER-TURN VALVE WITH ARRESTER WITH 1/2" MIP/SWEAT CONNECTION, 1/4" O.D. COMPRESSION OUTLET. VALVES COMPLY WITH ASME A112.18.1. USE 696RG1010MF WHEN INSTALLED IN FIRE-RATED WALLS	–	696-G1010MF
					696RG1010MF
	LB-1	LAVATORY OUTLET BOX	SIOUX CHIEF 696-G2011MF OXBOX LAVATORY OUTLET BOX, QUARTER-TURN VALVES WITH ARRESTERS WITH 1/2" MIP/ SWEAT CONNECTION, 3/8" O.D. COMPRESSION OUTLETS. VALVES COMPLY WITH ASME A112.18.1. MOUNT BOTTOM OF LAVATORY OUTLET BOX EVEN WITH P-TRAP WASTE ARM. USE 696-EX FRAME EXTENSION FOR THICKER WALLS. USE 696RG2011MF WHEN INSTALLED IN FIRE-RATED WALLS	–	696-G2011MF
					696RG2011MF
	KB-1	KITCHEN SUPPLY OUTLET BOX	SIOUX CHIEF 696-G3021MR KITCHEN SUPPLY OUTLET BOX, QUARTER-TURN VALVES WITH ARRESTERS WITH 1/2" MIP/ SWEAT CONNECTION, 3/8" O.D. COMPRESSION OUTLETS. THE THIRD VALVE IS FOR DISHWASHER HOT WATER. VALVES COMPLY WITH ASME A112.18.1. MOUNT BOTTOM OF LAVATORY OUTLET BOX EVEN WITH P-TRAP WASTE ARM. USE 696-1F FRAME. USE 696RG3021MF WHEN INSTALLED IN FIRE-RATED WALLS	–	696-G3021MR
					696RG3021MR
	TMV-1	THERMOSTATIC MIXING VALVE AND OUTLET BOX	SIOUX CHIEF 696-T2001PR THERMOSTATIC MIXING VALVE OUTLET BOX WITH 1/2" MALE SWEAT INLET CONNECTION, INTEGRAL ISOLATION VALVES, INTERNAL CHECK VALVE AND STAINLESS STEEL MESH DEBRIS SCREEN. ASSE 1070 COMPLIANT. USE 696-1F FRAME. FLUSH SUPPLY LINES AT START UP. CAPABLE OF 1.6 GPM WITH A 20 PSI DIFFERENTIAL AND A MINIMUM FLOW RATE OF 0.25 GPM. SET TEMPERATURE TO 110F FOR DUAL TEMPERATURE LAVATORIES AND HAND SINKS, 100F FOR SINGLE TEMPERATURE LAVATORIES AND HAND SINKS. MOUNT BELOW THE PLUMBING FIXTURE WHERE INDICATED ON PLAN(S). USE 696RT2001PF WHEN INSTALLED IN FIRE-RATED WALLS	–	696-T2001PR
					696RT2001PF
	AAV-1	AIR ADMITTANCE VALVE AND OUTLET BOX	SIOUX CHIEF 250-696122P AIR ADMITTANCE VALVE WITH DUAL FIT ADAPTER FOR 1-1/2" AND 2" VENT PIPE WITH OXBOX KIT. MEETS ASSE 1050 & 1051. ABS HOUSING AND ACTUATING DEVICE WITH ELASTROMERIC SEALING MEMBRANE AND PVC CONNECTOR, 2" INLET AND ATMOSPHERIC PORT. USE 250-696R122P WHEN INSTALLED IN FIRE-RATED WALLS	2"	250-696122P
					250-696R122P
	GOB-1	GAS VALVE OUTLET BOX	SIOUX CHIEF 696-1021GF GAS OUTLET BOX WITH 1/2" NPT VALVE AND ADAPTER FOR BLACK IRON PIPE. USE 696R1021GF FOR FIRE-RATED WALLS. USE 696-1031GF FOR 3/4" NPT VALVE.	–	696-1021GF
			1/2" NPT VALVE & ADAPTER FIRE-RATED 696R1021GF	–	696R1021GF
			3/4" NPT VALVE & ADAPTER 696-1031GF	–	696-1031GF
			3/4" NPT VALVE & ADAPTER FIRE-RATED 696R1031GF	–	696R1031GF

Project Name:

Project No:

Project Date:

General Notes:

Supply Pipe Material:

DWV Pipe Material:

Design Rainfall Rate:

Revision Date:

siouxchief.com

Sioux Chief Manufacturing
14940 Thunderbird Rd
Kansas City, MO 64147